

4 Pole Switch Disconnectors IP66/67



- red/yellow padlockable handle.
- insulated enclosure, grey, RAL7035.
- earth terminal included.
- switch interlocked with lid to prevent opening in 'ON' position.

Newbury Part Nos

NEW204P

NEW324P

NEW634P

NEW1004P

Dimensional Data (mm)		NEW204P	NEW324P	NEW634P	NEW1004P
H	(mm)	120	120	190	250
W	(mm)	85	85	100	145
D	(mm)	90	90	93	107
Cable Entries		4x20/25mm KO	4x20/25mm KO	4x25mm KO	4x40mm KO
Electrical Rating Date IEC 60947		NEW204P	NEW324P	NEW634P	NEW1004P
Enclosed Rating I_{the}	A	20	32	63	100
Insulation Voltage U_i	V	690	690	690	690
Rated Operating Current AC-21A @ 690V	A	20	32	63	100
Operational Power 3phase					
AC-3 220-240V	kW	2.2	5.5	11	18.5
AC-3 380-415V	kW	3.7	7.5	18.5	30
AC-23A 220-240V	kW	3	5.5	11	22
AC-23A 380-415V	kW	5.5	11	22	37
Short Circuit Protection					
Max. Fuse gL/gG	A	20	35	63	100
Terminal Capacity					
Single Core /Stranded Wire		2.5mm ²	6mm ²	16mm ²	50mm ²
Flexible Wire with sleeve		1.5mm ²	4mm ²	10mm ²	35mm ²