




**CABLEWORLD**  
SUPPLIERS OF ELECTRICAL CABLES & ACCESSORIES



### PVC insulated & sheathed cable

Class 5 flexible plain annealed Cu conductor, poly-vinyl chloride (PVC) insulation, poly-vinyl chloride (PVC) outer sheath.

Flexible single core cabling generally used for DC power supplies in the telecoms industry and other power supply applications where a flexible cable is required.

Voltage Grade:	450/750v to 35sqmm 600/1000v 50sqmm+
Temperature Range:	-15°C to +70°C fixed (minimum installation 0°C)
Minimum Bending Radius:	4 x OD
UV Resistant:	No
Approvals:	Gen. to BS6004 (to 35sqmm) IEC60502-1 (50sqmm+) IEC60332-1-2

No. of Cores	Size (sqmm)	Approx. OD (mm)	Weight (kg/km)
1	6	7.5	100
1	10	8.7	150
1	16	9.8	215
1	25	11.6	305
1	35	12.7	405
1	50	15.0	580
1	70	16.8	765
1	95	19.2	1010
1	120	21.3	1270
1	150	23.2	1570
1	185	25.6	1900
1	240	28.7	2445
1	300	31.5	3055

*All figures quoted are approximate*

Colours Available	
Standard	Blue, Grey
Optional	Dark Blue, Red, Green/Yellow