

Data sheet

Hydraulic data

Maximum operating pressure P_N	10 bar
Flow max $Q_{\max}$	3.6 m ³ /h
Minimum suction head at 50 °C m	0.5 m
Minimum suction head at 95 °C m	3.0 m
Minimum suction head at 110 °C	10.0 m
Min. fluid temperature $T_{\min}$	-10 °C
Max. fluid temperature $T_{\max}$	95 °C
Max. fluid temperature for max. ambient temperature of +25 °C $T_{\max}$	95 °C
Max. fluid temperature for max. ambient temperature of +40 °C $T_{\max}$	95 °C
Min. ambient temperature $T_{\min}$	-10 °C
Max. ambient temperature $T_{\max}$	40 °C

Motor data

Energy efficiency index (EEI)	0.20
Mains connection	1~230 V $\pm$ 10%, 50/60 Hz
Min. speed $n_{\min}$	700 1/min
Max. speed $n_{\max}$	4200 1/min
Power consumption $P_{1\min}$	3.0 W
Power consumption $P_{1\max}$	40.0 W
Interference emission	EN 61000-6-3
Interference immunity	EN 61000-6-2
Electromagnetic compatibility	EN 61800-3
Threaded cable connection	1 x PG11
Insulation class	F
Protection class	IPX2D


Materials

Pump housing	Cast iron
Impeller	PP-GF40
Shaft	Stainless steel
Bearing	Carbon, metal-impregnated

Installation dimensions



Pipe connection on the pressure side DNd	G 1½
Pipe connection on the suction side DNs	G 1½
Port-to-port length LO	180 mm

Pump curves



Dimensions and dimensions drawings

4215515_ConGraph_yonos_pico_row_180_dim_01_1708

**Wiring diagram**

Blocking current-proof motor

Single-phase motor (EM) 2-pole - 1~230 V, 50 Hz