



## TYPE 2 (BLACK) BRACKETS



These flat-packed, self assembly brackets provide a professional finish to the installation of wall mounted outdoor condensing units and air source heat pumps. The Type 2 brackets have a crossbar allowing the uprights to be spaced exactly as required, and include wall spacers to help level the unit on uneven walls. All components receive a powder coating, with a scratch resistant, textured finish in a colour (RAL 7032) to match most brands of condensing units and domestic air source heat pumps.

### FEATURES

- Integral spirit level for easier, correct installation
- Uprights mount anywhere on the crossbar which enables the arm span to be adjusted easily
- Adjustable wall spacers to level the arms
- Safe working load up to 250kg
- Suitable to match most brands of condensing units and domestic air source heat pumps
- Extra long arms (up to 660mm available for larger condensing units)
- Textured finish in (RAL 7032)

### THE PACKAGE

- Crossbar with spirit level
- 2/3 x support arms
- 2/3 x uprights
- Fixings
- Installation instructions

### RELATED PRODUCTS

- All guards
- Collection trays

### WEATHER PROTECTION PROCESS

NB: Sea salts are very corrosive and affect both ferrous and non-ferrous metals. Coastal installations are particularly at risk as they are frequently exposed to sea salt solutions followed by dry periods, where this wet/dry cycle produces a very corrosive environment. We strongly recommend that in such locations only our stainless steel brackets are installed.



**PROCESS ONE**  
Corrosion resistant raw material, often referred to as Zintec



**PROCESS TWO**  
Zinc phosphating process multi stage cleaning and dipping chemical zinc



**PROCESS THREE**  
ED coating process: electrophoretic deposition (aka ED or EPD) coating



**PROCESS FOUR**  
Epoxy polyester powder coating

Part code	Description	Safe working load*	Max load	Crossbar	Upright	Support arm	Weight
CBR2-XL-BL	Type 2 Bracket - XL	250kg	500kg	1040mm	550mm	660mm	16.2kg
CBR2-XL-3A-BL	Type 2 Bracket - XL (3 arms)	250kg	500kg	1040mm	550mm	660mm	21.5kg
CBR2-XXL-BL	Type 2 bracket - Double XL	200kg	400kg	1040mm	550mm	780mm	17.5kg
CBR2-XXL-3A-BL	Type 2 Bracket - Double XL (3 arms)	200kg	400kg	1040mm	550mm	780mm	22.5kg
CBR2-XXL-3A-BL-D	Type 2 Bracket - Double XL (3 arms)	200kg	400kg	1120mm	550mm	780mm	22.5kg

\*All brackets are tested to twice the safe working loads at an independent UK facility.

## BRACKETS TYPE 2 BRACKETS

(black)

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to [sales@diversitech.com](mailto:sales@diversitech.com) or visit [www.diversitech.global](http://www.diversitech.global)



Glaisdale Drive East  
Nottingham NG8 4LY  
United Kingdom