



The GivEnergy Hybrid Inverter is a battery and solar inverter in one unit.

It can be coupled directly with solar panels to generate usable electricity in the property as well as storing any excess energy for later use in a battery. The Hybrid Inverter aims to minimise export by store excess energy in the battery during generation hours. Additionally, it will minimise import by discharging to meet demand in the property.



Remote Firmware

Control and monitor your Smart System on the move via our GivEnergy Monitoring App and Portal.



New Solar Installations

Replace your old storage system with a brand new Smart System and gain the benefits of renewable energy.



Flexible Rate Tariff

Charge from the grid at off-peak times where energy is cheaper, and discharge at peak times where energy is more expensive.



5 Year Warranty

Supplied with a full manufacturers warranty, extendable to 10 years. Our UK team are on hand to help you should any issues arise.

Hybrid Inverter 3.6

Gen 1

INPUT DATA (PV)

Max. DC Power	4700W
Max. DC Voltage	580V
Start-up Voltage	140V VOC (120V Vmpp)
DC Nominal Voltage	360V
PV Nominal Voltage	120V - 580V
MPPT Voltage Range	120V - 550V
Max. Input Current (per string)	11A
Max. Short Circuit Current (per string)	20A
Number of Independent MPPT Input	2

OUTPUT DATA (AC)

Nominal AC Output Power	3600W
Max. Apparent Power	3680VA
Max. Output Current	16A
AC Voltage	180V - 280V
AC Grid Frequency Range	50±5Hz
Power Factor at Rated Power	1
Power Factor	0.9 Lagging... 0.9 Leading
THDI	<3%
AC Connection	Single Phase (multiple units can be installed for 3 phase)

BATTERY

Nominal Power	2600W
Max. Charging / Discharging Current	50A / 50A

BACKUP OUTPUT

Max. Power Output (Battery + Solar)	3600W
Max. Power Output from Battery	2600W
Output Frequency	50 Hz
Output Voltage	230V

PROTECTION DEVICES

DC Reverse Polarity Protection	Yes
DC Switch Rating for each MPPT	Yes
Output Over Current Protection	Yes
Output Overvoltage Protection Varistor	Yes
Ground Fault Monitoring	Yes
Grid Monitoring	Yes
Max. Inrush Current	30A Peak
Max. Output Fault Current	40A Peak
Max. Output Overcurrent Protection	25A RMS
Earth Leakage Current Monitoring	Yes

GENERAL DATA

Dimensions	440H x 260D x 480W (mm)
Weight	24 Kg
Operating Temperature Range	-25°C > 55°C (Ambient)
Consumption Operating (Standby) / Night	<5W / <0.5W
Topology	Transformerless
Cooling Concept	Natural
Environmental Protection Rating	IP65

FEATURES

PV Connection	H4 / MC4
Battery Connection	Screw Terminal
AC Connection	Screw Terminal
Display	LED
Interfaces: WiFi / USB / GPRS / RS485 / 4G	Opt / Yes / Opt / Yes / Opt
Warranty	Yes / Opt

CERTIFICATES AND APPROVALS

AA4777,
VDE-AR-N4105,
VDE0126,
G98,
IEC2109-1-2,
IEC62040,
EN61000-6-2,
EN61000-6-3,
EN50549,
G100