



EPS 3PH-4UNIT

THREE-PHASE



- PC, Robust metal enclosure IP65
- Applied to residential, commercial solar installations
- Compatible with H3/AIO H3/H3 Smart inverter
- Automatically switch to On-Grid/Off-Grid state



Max. input current
(per phase) 80A



Safety



IP65
Rated



Easy
Installation



For more information about the Fox ESS range, visit:
www.fox-ess.com



TECHNICAL SPECIFICATIONS

MODEL	EPS 3PH-4UNIT
GRID INPUT	
Rated Voltage [VAC]	220 / 380, 230 / 400, 3L / N / PE
Rated Frequency [Hz]	50 / 60
Max. Input Current (Per Phase) [A]	80
EPS INPUT	
Rated Voltage [VAC]	220 / 380, 230 / 400, 3L / N / PE
AC frequency [Hz]	50 / 60
Max. input current (per phase) [A]	20
Number of groups	4
EPS LOAD	
Rated Voltage [VAC]	220 / 380, 230 / 400, 3L / N / PE
Rated Frequency [Hz]	50 / 60
Max. Output Current [A]	80
GENERAL DATA	
Cooling concept	Natural
Installation	Wall-mounted
Operating temperature range [°C]	-25 ~ +50
Dimensions(W*H*D) [mm]	336*306*138
Dimensions of packing(W*H*D) [mm]	440*345*205
Net Weight [Kg]	6
Gross Weight [Kg]	7
Ingress protection	IP65

