

SUNGROW
ACCESSOIRES
COMPATIBILITY LIST

COMPATIBILITY LIST

SG2.0-6.0RS



Communication

	Part of delivery	Max. Support	Features / Comment
WiNet-S	yes	max. 1 device	10 sec. refresh, WiFi or Ethernet

Energy Meters

	Part of delivery	Feed-in limitation	Features / Comment
S100	no	max. 1 S100	

COMPATIBILITY LIST

SG3.0-20RT



Communication

	Part of delivery	Max. Support	Features / Comment
WiNet-S	yes	max. 1 device	10 sec. refresh, WiFi or Ethernet
COM100E	no	max. 5 devices*	FTP push, connecting environm. sensors, daisy chain mode, WiFi or Ethernet

Energy Meters

	Part of delivery	Feed-in limitation	Features / Comment
DTSD1352 80A**	no	max. 1 device	
DTSD1352 6A**	no	max. 5 devices*	CT to be bought from 3rd party manufacturer, feed-in limitation supported by COM100E
Janitza (UMG604, UMG104)	no	max. 5 devices*	to be bought from 3rd party manufacturer, feed-in limitation supported by COM100E
Weidmüller (EM610)	no	max. 5 devices*	to be bought from 3rd party manufacturer, feed-in limitation supported by COM100E

* devices: inverters, energy meters, and irradiation sensors

** only with meter version bought from Sungrow

COMPATIBILITY LIST

SH3.0-6.0RS



Communication


	Part of delivery	Max. Support	Features / Comment
WiNet-S	yes	max. 1 device	10 sec. refresh, WiFi or Ethernet

Energy Meters

	Part of delivery	Feed-in limitation	Features / Comment
S100	yes	max. 1 device	

COMPATIBILITY LIST

SH5.0-10RT



Communication

	Part of delivery	Max. Support	Features / Comment
WiNet-S	yes	max. 1 device	10 sec. refresh, WiFi or Ethernet

Energy Meters

	Part of delivery	Feed-in limitation	Features / Comment
DTSU666*	yes	yes 1 per host inverter	
DTSD1352 80A*	no	yes 1 per host inverter	
DTSD1352 6A*	no	yes 1 per host inverter	CT to be bought from 3rd party manufacturer

* only with meter version bought from Sungrow

COMPATIBILITY LIST

SG33-110CX



Communication

	Part of delivery	Max. Support	Features / Comment
WiNet-S	no	max. 1 device	10 sec. refresh, WiFi or Ethernet
COM100E	no	max. 30 devices*	FTP push, connecting environm. sensors, daisy chain mode, IV curve scan, WiFi or Ethernet
EyeM4	no	max. 10 devices*	Daisy chain mode, WiFi

Energy Meters

	Part of delivery	Feed-in limitation	Features / Comment
DTSD1352 6A**	no	Logger: max. 30 devices* (SG33-50CX) Logger: max. 25 devices* (SG110CX) EyeM4: max. 10 devices*	CT to be bought from 3rd party manufacturer, feed-in limitation supported by COM100E or EyeM4
Janitza (UMG604, UMG104)	no	Logger: max. 30 devices* EyeM4: max. 10 devices*	to be bought from 3rd party manufacturer, feed-in limitation supported by COM100E or EyeM4
Weidmüller (EM610)	no	Logger: max. 30 devices* EyeM4: max. 10 devices*	to be bought from 3rd party manufacturer, feed-in limitation supported by COM100E or EyeM4

* devices: inverters, energy meters, and irradiation sensors (for COM100E only)

** only with meter version bought from Sungrow