


## Nexa TOPCon N-type

FRONT SIDE

# 500 - 515 W

› Double Glass Bifacial



+23.1%

### Module efficiency

Module efficiency up to 23.16 %



### Bifacial cell

Bifaciality factor: 80 ± 5 %



### Hail resistance

RG3/HW3 certified



### Better temperature coefficient

Minimized thermal losses, improved efficiency



### PFAS free

Product free from perfluoroalkyl and polyfluoroalkyl substances



### Sustainable product

High percentage of recyclable materials

# 25

Years

Product Warranty

+5 years for Premium Partners

# 30

Years

Performance Warranty

Linear Warranty

1% First year degradation

0.38% Annual degradation

88% Power in year 30

### Light up your world with Eurener

Eurener's extensive portfolio of certifications and awards is testament to our unwavering commitment to our partners and our deep sense of social and ethical responsibility.



Spanish Quality  
Worldwide





Awarded as TOP Brand PV  
in 6 countries for 6th year



EcoVadis  
Platinum Medal



# Eurener MEPV — NEXA Double Glass Bifacial 500-515W



### Mechanical specification

Solar cells	N-Type bifacial monocrystalline silicon cells
Front Glass	2 mm anti-reflective surface tempered solar glass
Back Glass	2 mm tempered solar glass
Frame	Black anodized aluminium
Junction Box	IP68, 3 by-pass diodes
Connector	Original MC4-Evo 2
Cable	1200 mm (±20%) length and 4 mm <sup>2</sup> section
Dimension	1961 x 1134 x 30 mm (±1%)
Area	2.22 m <sup>2</sup>
Weight	27.5 kg
Packaging	864 pcs/truck

### Temperature coefficients

Temperature coefficient of Isc (α)	0.046 %/°C
Temperature coefficient of Voc (β)	-0.25 %/°C
Temperature coefficient of Pmax (γ)	-0.29 %/°C
Temperature range	-40 °C ~ +85 °C
Nominal operating cell temperature (NOCT)	45 ± 2 °C

	MEPV 500		MEPV 505		MEPV 510		MEPV 515	
Electrical characteristics	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Nominal power. Pmax	500 Wp	382 Wp	505 Wp	386 Wp	510 Wp	389 Wp	515 Wp	392 Wp
Short-circuit current (Isc)	15.86 A	12.79 A	15.90 A	12.82 A	15.94 A	12.85 A	15.98 A	12.88 A
Open-circuit voltage (Voc)	40.10 V	38.10 V	40.32 V	38.30 V	40.53 V	38.50 V	40.72 V	38.70 V
Maximum power current (Imp)	15.02 A	12.17 A	15.08 A	12.20 A	15.14 A	12.23 A	15.30 A	12.26 A
Maximum power voltage (Vmp)	33.30 V	31.41 V	33.51 V	31.60 V	33.70 V	31.81 V	33.99 V	31.99 V
Module efficiency	22.48 %		22.71 %		22.93 %		23.16 %	

Electrical characteristics	Bifacial gain 10%							
Nominal power. Pmax	550 Wp		556 Wp		561 Wp		567 Wp	
Short-circuit current (Isc)	17.43 A		17.49 A		17.55 A		17.60 A	
Open-circuit voltage (Voc)	40.05 V		40.30 V		40.55 V		40.80 V	
Maximum power current (Imp)	16.51 A		16.58 A		16.63 A		16.70 A	
Maximum power voltage (Vmp)	33.33 V		33.55 V		33.74 V		33.96 V	

\* STC: 1000 W/m<sup>2</sup>, module temperature 25°C, AM 1.5  
 \* NOCT: 800 W/m<sup>2</sup>, ambient temperature 20°C, AM 1.5

Operating parameters	
Maximum voltage	1500 V
Maximum series fuse rating. Ir	25 A
Power output tolerance	0 - + 3 %
Voc and Isc tolerance	± 3 %
Fire rating	Class A (UL 790)
Protection class	Class II (IEC 61140)
Mechanical loads	Front load 5400 Pa, Back load 2400 Pa

### Corporate and product certificates

ECOVADIS rating - Platinum Medal (TOP 1%)
Solar Industry Forced Labor Prevention Pledge by SEIA
ISO9001:2015 - Quality Management Systems
ISO14001:2015 - Environmental Management System
WEEE compliance in Germany
PV CYCLE Italy
IEC 61215 - Terrestrial photovoltaic (PV) modules - Design qualification and type approval
IEC 61730 - Photovoltaic (PV) module safety qualification
IEC 61701 - Photovoltaic (PV) modules - Salt mist corrosion testing
IEC 62716 - Photovoltaic (PV) modules - Ammonia corrosion testing
IEC TS 62804 - Photovoltaic (PV) modules - Test methods for the detection of potential-induced degradation
Hail resistance HW3/RG3
Certificate of Factory Production Control (UK) - MCS
Fire reaction class: 1 - LAPI



NOTE: Read the safety and installation manual before using the product. This data sheet is not legally binding, Eurener reserves the right of final interpretation. Eurener reserves the right to change the product characteristics and/or specifications without prior notice. The latest versions of all documents can always be found on our website at [www.eurener.com](http://www.eurener.com).

**SINCE 1997**  
 more than energy

**eurener.com**  
 contact@eurenerworld.com  
 +34 960 045 515  
 Calle Colón, 1-23  
 46004, Valencia. Spain

**European experts in residential modules**

Since 1997 our main purpose has been to supply quality and long-lasting photovoltaic modules that allow us and future generations, to continue generating clean energy to take care of our planet.