



Electric Vehicle Gel

HAZE

POWER TO KEEP YOU ON THE MOVE

ELECTRIC VEHICLE applications are wide and varied with many durability & power demands placed firmly on the batteries shoulders.



HAZE ELECTRIC VEHICLE GEL always delivers when you need it, whatever your DC requirement in extreme situations.



Tough ABS case with INSERT TERMINALS as standard, smaller sizes with FASTON.



Gel Technology delivers cranking amps, general power and long/deep discharges without the need for immediate recharge. EXTRA LONG CYCLE LIFE and resistance to mechanical stress and the elements all in one battery.



HAZE ELECTRIC VEHICLE GEL delivers maximum capacity within twenty cycles and keeps delivering long after the others are on the scrap heap. HAZE R&D has resulted in SPECIAL CHEMICAL and PROCESS technology to ensure consistency and performance.



The Quality & Management system governing the manufacture of this product is ISO 9001:2000 and ISO 14001:2004 certified.



Important Note: The capacities and runtimes quoted below are applicable to a battery which has achieved full capacity. Full capacity is achieved after approx. 20 cycles. Initial capacity will be approx. 15 - 20% lower.

Battery Model	Dimensions (mm) & weight (Kg)						Cold Cranking Amps			Volts	Thread size mm	Reserve Capacity - Minutes Discharged					Capacity - Ampere Hour*						
	Length	Width	Height Auto Post	Height Insert/Tab	Battery Height	Weight	20°C (68°F)	0°C (32°F)	-18°C (0°F)			75 Amps	25 Amps	20 Amps	15 Amps	8 Amps	100 Hr	48 Hr	20 Hr	10 Hr	5 Hr	3 Hr	1 Hr
HZY-EV6-7.5	150	34	-	100	94	1.2	-	-	-	6	NA	-	-	-	-	-	8.8	8.3	7.7	7.1	6.2	5.7	4.7
HZY-EV6-10	151	50	-	101	95	1.8	-	-	-	6	NA	-	-	-	-	-	11.6	10.9	10.3	9.4	8.4	7.8	6.3
HZY-EV6-12	151	50	-	103	95	1.8	-	-	-	6	NA	-	-	-	-	-	14.1	13.2	12.3	11.2	10.3	9.2	7.5
HZY-EV12-7.5	151	65	-	100	94	2.4	-	-	-	12	NA	-	-	-	-	-	8.8	8.3	7.7	7.1	6.2	5.7	4.7
HZY-EV12-12	151	98	-	106	98	3.7	-	-	-	12	NA	-	-	-	-	-	14.1	13.2	12.3	11.2	10.3	9.2	7.5
HZY-EV12-18	181	76	-	157	167	5.6	204	137	84	12	5	-	-	26	45	93	20.4	19.1	17.7	16.4	14.7	13.5	11.2
HZY-EV12-18EX	181	77	-	170	170	6.8	298	214	137	12	5	4.8	28	38	54	115	23.5	23.1	22.4	20.7	18.7	17.1	13.9
HZY-EV12-26	168	178	-	117	124	9.2	301	217	142	12	5	-	23	41	66	144	29.6	27.8	26.3	24.0	22.2	20.4	16.2
HZY-EV12-33	195	130	-	151	160	10.5	350	260	172	12	6	6.9	30	53	77	173	41.9	39.3	36.4	32.5	28.3	25.7	20.4
HZY-EV12-44	198	167	175	158	157	13.5	450	337	220	12	6	12	55	80	115	242	52.2	49.0	45.4	41.1	36.8	34.3	27.4
HZY-EV12-55	229	138	231	214	213	17.7	569	444	294	12	6	19	86	120	168	351	68.7	64.5	59.7	54.9	49.7	45.4	36.7
HZY-EV12-60-2	260	168	197	180	179	17.5	572	459	303	12	6	22	90	123	169	360	61.2	58.5	54.2	51.1	45.3	40.9	32.1
HZY-EV12-60	260	168	197	180	179	22.1	686	563	420	12	6	28	115	155	218	458	82.4	77.5	71.6	64.1	57.2	50.2	39.4
HZY-EV12-70J	349	168	193	176	175	22.6	663	530	367	12	6	27	117	159	218	460	82.2	77.2	71.5	63.9	57.8	52.9	45.3
HZY-EV12-65	279	175	190	173	190	22.7	708	573	400	12	6	32	135	180	251	519	86.3	81.0	75.0	68.6	61.1	56.4	46.4
HZY-EV12-65B	279	175	190	173	190	25.9	721	584	412	12	6	35	150	195	268	545	90.4	88.7	86.1	76.9	68.0	61.8	50.2
HZY-EV12-70	260	168	229	212	211	24.2	718	581	410	12	8	31	140	180	247	542	89.9	88.2	85.6	76.6	67.5	61.2	49.5
HZY-EV12-80	260	168	229	212	211	24.4	740	600	425	12	8	33	144	195	270	560	97.0	91.1	87.9	79.0	71.0	65.5	54.2
HZY-EV12-100	306	168	229	212	211	28.5	820	715	520	12	8	45	174	230	324	672	121	114	105	92.6	80.9	74.2	61.1
HZY-EV12-110	329	173	227	210	209	30.9	854	766	560	12	8	49	188	253	363	750	136	128	119	106	94.0	85.2	67.9
HZY-EV12-120	408	176	-	209	227	34.8	917	835	650	12	8	61	225	288	414	864	140	131	122	108	96.5	90.2	73.6
HZY-EV12-135	340	173	303	286	283	41.8	998	906	762	12	8	84	276	368	519	1064	186	174	161	146	133	122	96.8
HZY-EV12-150	482	170	-	225	242	45.0	1011	919	784	12	8	88	288	384	540	1110	183	172	159	145	130	121	100
HZY-EV12-160	530	209	234	217	214	54.0	1028	938	811	12	8	95	318	414	582	1200	220	206	191	175	158	144	110
HZY-EV12-200	520	240	240	225	220	63.0	1094	988	909	12	8	142	438	564	796	1654	282	265	246	228	205	186	134
HZY-EV12-230	521	269	223	208	203	74.5	1117	1007	940	12	8	167	528	678	915	1949	302	284	263	243	216	198	153
HZY-EV6-110	193	168	225	208	205	17.9	880	789	577	6	8	53	209	268	372	793	141	133	123	115	102	93.0	73.8
HZY-EV6-160	298	171	246	229	226	26.9	1059	966	835	6	8	111	342	444	624	1290	217	204	189	175	157	146	119
HZY-EV6-180	260	181	264	247	246	30.4	1071	972	868	6	8	120	366	474	666	1398	213	200	185	169	151	139	115
HZY-EV6-180-2	260	181	264	247	246	30.5	1090	980	890	6	8	138	420	555	741	1527	224	211	195	184	167	141	115
HZY-EV6-200	323	178	245	228	225	31.1	1083	978	900	6	8	133	402	516	720	1524	254	239	221	199	178	163	130
HZY-EV6-200-2	306	168	229	212	211	31.0	1080	976	895	6	8	131	400	513	717	1520	222	209	193	176	156	144	118
HZY-EV6-225	244	188	272	257	275	33.4	1116	1007	927	6	8	147	462	602	828	1770	253	238	220	201	179	165	136
HZY-EV6-245	260	180	283	268	263	34.0	1388	1108	850	6	8	160	559	721	974	1989	284	267	241	217	196	182	149
HZY-EV6-335	295	178	365	350	345	41.0	1650	1395	1228	6	8	193	726	924	1240	2395	360	345	320	284	259	234	194
HZY-EV8-160	260	182	315	298	295	36.4	1045	955	829	8	8	103	330	432	597	1176	181	170	157	144	128	118	97.2
HZY-EV8-160-2	260	182	292	270	266	29.8	951	869	754	8	8	92	294	384	531	1047	161	151	140	128	114	105	86


Battery Charging: To obtain the optimum cycle life performance from the Haze EV range it is vital that the correct charging profile is utilised. Haze specifies a charging profile with an equalizing/desulphation phase as detailed in the Haze document "Charging - Cyclic Applications" for flat pasted plates. Please request this literature from your Haze distributor.

Cycle Life: To ensure maximum cycle life it is recommended that the battery be fully recharged as soon as possible after use. Cycle life is very dependant on the depth of discharge (DOD). The following is a guide to the number of cycles expected. 100% DOD - 400 cycles, 75% DOD - 450 cycles, 50% DOD - 650 cycles.



Haze Battery Company keenly encourages environmental awareness; PLEASE follow guidelines for the recycling /disposal of lead.

190316



Website: www.hazebattery.com
E mail : sales@hazebattery.com