

2. Outdoor Units

2-9. Capacity table

2) Maximum Heating Capacity (Integrated Value)

LWT (Leaving Water Temp.), Tamb (Ambient Temp.), HC (Heating Capacity), PI (Power input), WF (Water Flow)

Model	Temp. (°C)	25			30			35			40			45			50			55			60			65			70			75				
		HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)					
AE050CXYBEK/EU	-25	3,850	1,980	11.1	3,695	1,970	10.6	3,540	1,950	10.2	3,470	1,990	10.0	3,390	2,020	9.8	3,350	2,110	9.7	3,310	2,220	7.0	3,250	2,290	7.0	3,190	2,380	7.0								
	-20	4,410	1,930	12.7	4,295	2,010	12.4	4,180	2,100	12.1	4,100	2,130	11.8	4,020	2,160	11.6	3,900	2,220	11.3	3,780	2,290	7.0	3,710	2,380	7.0	3,640	2,480	7.0								
	-15	4,900	1,850	14.1	4,815	2,000	13.9	4,730	2,180	13.6	4,620	2,190	13.3	4,520	2,210	13.1	4,410	2,290	12.8	4,300	2,390	7.8	4,220	2,480	7.7	4,140	2,590	7.0	4,040	2,610	7.0					
	-10	5,310	1,730	15.3	5,110	1,840	14.7	4,910	1,980	14.2	4,880	2,090	14.1	4,850	2,220	14.0	4,840	2,320	14.0	4,830	2,420	8.8	4,820	2,590	8.8	4,800	2,770	7.0	4,680	2,900	7.0	4,560	3,040	7.0		
	-7	5,380	1,550	15.5	5,165	1,650	14.9	4,950	1,770	14.3	4,950	1,900	14.3	4,950	2,040	14.3	4,950	2,210	14.4	4,940	2,410	9.0	4,920	2,590	8.9	4,900	2,800	7.1	4,900	2,980	7.2	4,890	3,190	7.2		
	-2	5,460	1,390	15.7	5,205	1,440	15.0	4,950	1,500	14.3	4,950	1,700	14.3	4,950	1,960	14.3	4,950	2,100	14.4	4,950	2,270	9.0	4,950	2,410	9.0	4,950	2,570	7.2	4,870	2,760	7.1	4,770	2,970	7.0		
	2	5,540	1,230	15.9	5,245	1,260	15.1	4,950	1,300	14.3	4,950	1,470	14.3	4,950	1,710	14.3	4,950	1,890	14.4	4,950	2,150	9.0	4,950	2,220	9.0	4,950	2,290	7.2	4,950	2,510	7.2	4,840	2,710	7.1		
	7	6,090	980	17.5	5,545	980	16.0	5,000	980	14.4	5,000	1,130	14.4	5,000	1,320	14.5	5,000	1,450	14.5	5,000	1,610	9.1	5,000	1,740	9.1	5,000	1,890	7.3	5,000	2,100	7.3	5,000	2,360	7.3		
	12	6,400	920	18.4	6,270	1,010	18.1	6,140	1,110	17.7	6,080	1,220	17.6	6,010	1,340	17.4	5,980	1,510	17.3	5,950	1,730	10.8	5,920	1,820	10.8	5,880	2,070	8.6	5,850	2,290	8.5	5,820	2,480	8.5		
	15	6,890	900	19.8	6,675	980	19.2	6,460	1,080	18.6	6,390	1,200	18.5	6,330	1,360	18.3	6,250	1,510	18.1	6,180	1,710	11.2	6,100	1,790	11.1	6,080	2,010	8.9	6,060	2,220	8.8	6,040	2,500	8.8		
	20	7,490	850	21.5	7,225	950	20.8	6,960	1,080	20.1	6,880	1,220	19.9	6,790	1,400	19.6	6,700	1,520	19.4	6,610	1,670	12.0	6,530	1,770	11.9	6,480	2,020	9.4	6,470	2,270	9.4	6,390	2,560	9.4		
	25	8,020	810	23.1	7,800	920	22.5	7,580	1,070	21.9	7,490	1,210	21.6	7,390	1,410	21.4	7,270	1,530	21.1	7,160	1,690	13.0	7,020	1,840	12.8	6,920	2,070	10.1	6,840	2,250	10.0	6,770	2,470	9.9		
30	8,510	770	24.5	8,305	880	23.9	8,100	1,030	23.4	7,990	1,190	23.1	7,880	1,400	22.8	7,820	1,530	22.7	7,750	1,700	14.1	7,690	1,880	14.0	7,620	2,120	11.1	7,550	2,280	11.0	7,410	2,460	10.8			
35	9,080	730	26.1	8,840	840	25.5	8,600	1,010	24.8	8,410	1,150	24.3	8,220	1,360	23.8	8,150	1,490	23.6	8,080	1,660	14.7	8,020	1,840	14.6	7,950	2,050	11.6	7,850	2,200	11.5	7,690	2,350	11.3			
AE080CXYBEK/EU	-25	5,700	3,020	16.4	5,475	3,000	15.8	5,250	2,980	15.1	5,135	3,030	14.8	5,020	3,080	14.5	4,960	3,220	14.4	4,900	3,380	8.9	4,810	3,500	8.7	4,720	3,630	7.0								
	-20	6,600	2,970	19.0	6,425	3,090	18.5	6,250	3,230	18.0	6,130	3,270	17.7	6,010	3,320	17.4	5,830	3,420	16.9	5,650	3,530	10.2	5,550	3,670	10.1	5,450	3,820	7.9								
	-15	7,400	2,880	21.3	7,270	3,110	20.9	7,140	3,380	20.6	6,980	3,400	20.2	6,820	3,430	19.7	6,655	3,560	19.3	6,490	3,710	11.8	6,370	3,860	11.6	6,250	4,030	9.1	6,100	4,070	8.9					
	-10	8,020	2,690	23.1	7,715	2,860	22.2	7,410	3,070	21.4	7,365	3,250	21.3	7,320	3,460	21.2	7,310	3,600	21.2	7,300	3,760	13.2	7,275	4,020	13.2	7,250	4,350	10.6	7,070	4,510	10.3	6,890	4,740	10.1		
	-7	8,120	2,410	23.4	7,810	2,570	22.5	7,500	2,780	21.6	7,490	2,970	21.6	7,480	3,180	21.6	7,465	3,440	21.6	7,450	3,740	13.5	7,425	4,020	13.5	7,400	4,350	10.8	7,390	4,630	10.8	7,380	4,950	10.8		
	-2	8,240	2,170	23.7	8,020	2,290	23.1	7,800	2,430	22.5	7,825	2,760	22.6	7,850	3,200	22.7	7,775	3,400	22.5	7,700	3,630	14.0	7,600	3,810	13.8	7,500	4,010	10.9	7,350	4,290	10.7	7,200	4,620	10.5		
	2	8,360	1,910	24.0	8,155	2,020	23.5	7,950	2,150	22.9	7,950	2,430	23.0	7,950	2,790	23.0	7,950	3,120	23.0	7,950	3,550	14.4	7,800	3,600	14.2	7,650	3,650	11.1	7,475	3,900	10.9	7,300	4,210	10.7		
	7	9,190	1,520	26.4	8,595	1,570	24.7	8,000	1,630	23.1	8,000	1,860	23.1	8,000	2,160	23.1	8,000	2,390	23.2	8,000	2,670	14.5	8,000	2,870	14.5	8,000	3,110	11.6	8,000	3,460	11.7	8,000	3,880	11.7		
	12	9,850	1,470	28.3	9,650	1,600	27.8	9,450	1,770	27.2	9,350	1,930	27.0	9,250	2,130	26.8	9,200	2,390	26.7	9,150	2,730	16.6	9,100	2,890	16.5	9,050	3,280	13.2	9,000	3,630	13.1	8,950	3,930	13.1		
	15	10,400	1,390	29.9	10,075	1,520	29.0	9,750	1,680	28.1	9,650	1,870	27.9	9,550	2,110	27.6	9,440	2,350	27.4	9,330	2,670	16.9	9,210	2,780	16.7	9,180	3,120	13.4	9,150	3,450	13.4	9,110	3,880	13.3		
	20	11,300	1,320	32.5	10,905	1,480	31.4	10,510	1,680	30.3	10,380	1,900	30.0	10,250	2,180	29.7	10,115	2,370	29.3	9,980	2,600	18.1	9,860	2,760	17.9	9,800	3,140	14.2	9,760	3,530	14.2	9,650	3,990	14.1		
	25	12,110	1,270	34.8	11,775	1,430	33.9	11,440	1,660	33.0	11,300	1,880	32.6	11,160	2,190	32.3	10,980	2,390	31.8	10,800	2,620	19.6	10,600	2,860	19.3	10,450	3,210	15.2	10,320	3,490	15.1	10,220	3,840	15.0		
30	12,850	1,200	37.0	12,535	1,370	36.1	12,220	1,610	35.2	12,060	1,840	34.8	11,900	2,180	34.4	11,800	2,380	34.2	11,700	2,640	21.2	11,600	2,930	21.1	11,500	3,290	16.7	11,400	3,540	16.6	11,300	3,690	15.8			
35	13,700	1,140	39.4	13,340	1,310	38.4	12,980	1,570	37.4	12,690	1,790	36.6	12,400	2,110	35.9	12,300	2,320	35.7	12,200	2,580	22.1	12,100	2,850	22.0	12,000	3,190	17.5	11,100	3,200	16.2	11,100	3,180	14.8			
AE080CXYBGK/EU	-25	5,700	3,020	16.4	5,475	3,000	15.8	5,250	2,980	15.1	5,135	3,030	14.8	5,020	3,080	14.5	4,960	3,220	14.4	4,900	3,380	8.9	4,810	3,500	8.7	4,720	3,630	7.0								
	-20	6,600	2,970	19.0	6,425	3,090	18.5	6,250	3,230	18.0	6,130	3,270	17.7	6,010	3,320	17.4	5,830	3,420	16.9	5,650	3,530	10.2	5,550	3,670	10.1	5,450	3,820	7.9								
	-15	7,400	2,880	21.3	7,270	3,110	20.9	7,140	3,380	20.6	6,980	3,400	20.2	6,820	3,430	19.7	6,655	3,560	19.3	6,490	3,710	11.8	6,370	3,860	11.6	6,250	4,030	9.1	6,100	4,070	8.9					
	-10	8,020	2,690	23.1	7,715	2,860	22.2	7,410	3,070	21.4	7,365	3,250	21.3	7,320	3,460	21.2	7,310	3,600	21.2	7,300	3,760	13.2	7,275	4,020	13.2	7,250	4,320	10.6	7,070	4,580	10.3	6,890	4,890	10.1		
	-7	8,120	2,410	23.4	7,810	2,570	22.5	7,500	2,780	21.6	7,490	2,970	21.6	7,480	3,180	21.6	7																			

2. Outdoor Units

2-9. Capacity table

2) Maximum Heating Capacity (Integrated Value)

LWT (Leaving Water Temp.), Tamb (Ambient Temp.), HC (Heating Capacity), PI (Power input), WF (Water Flow)

Model	Tamb (°C)	25			30			35			40			45			50			55			60			65			70			75							
		HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)	HC (W)	PI (W)	WF (LPM)								
AE160CXYBEK/EU	-25	9,800	4,830	28.2	10,650	5,630	30.7	11,500	6,570	33.2	11,050	6,680	31.9	10,600	6,790	30.7	10,370	6,950	30.1	9,800	6,950	17.8	9,390	6,950	17.1	8,800	6,720	12.8											
	-20	13,300	6,240	38.3	13,135	6,570	37.8	12,970	6,940	37.4	12,400	6,940	35.8	11,830	6,950	34.2	11,460	6,950	33.2	11,100	6,940	20.1	10,190	6,940	18.5	9,760	6,920	14.2											
	-15	14,980	6,350	43.1	14,370	6,620	41.4	13,760	6,950	39.7	13,390	6,950	38.7	13,010	6,950	37.6	12,630	6,950	36.6	11,880	6,950	21.5	11,070	6,950	20.1	10,680	6,960	15.6	9,800	6,710	14.3								
	-10	15,000	5,880	43.1	14,380	6,030	41.4	13,750	6,190	39.6	13,400	6,490	38.7	13,050	6,830	37.8	12,650	6,840	36.7	12,200	6,850	22.1	11,770	6,770	21.4	11,100	6,770	16.2	10,660	6,940	15.6	9,940	6,900	14.5					
	-7	14,800	5,150	42.6	14,400	5,360	41.5	14,000	5,600	40.4	13,960	6,080	40.3	13,910	6,640	40.2	13,800	6,830	40.0	12,820	6,850	23.2	12,000	6,770	21.8	11,140	6,750	16.2	10,900	6,900	15.9	10,050	6,930	14.7					
	-2	14,500	4,460	41.7	14,630	4,740	42.1	14,760	5,050	42.6	14,690	5,730	42.4	14,610	6,610	42.3	14,300	6,590	41.5	13,400	6,450	24.3	12,840	6,770	23.3	12,140	6,750	17.7	11,300	6,770	16.5	10,300	6,780	15.1					
	2	14,200	3,790	40.8	14,850	4,210	42.8	15,500	4,700	44.7	15,250	5,210	44.0	15,000	5,880	43.4	14,600	6,120	42.3	14,000	6,060	25.4	13,930	6,770	25.3	13,450	6,750	19.6	12,300	6,760	18.0	11,500	6,760	16.8					
	7	17,500	3,110	50.3	16,750	3,310	48.2	16,000	3,550	46.2	16,000	4,000	46.2	16,000	4,570	46.3	16,000	4,940	46.4	16,000	5,520	29.0	16,000	5,930	29.1	16,000	6,540	23.3	14,890	6,910	21.7	13,400	6,910	19.6					
	12	18,520	3,050	53.3	18,150	3,290	52.3	17,770	3,580	51.2	17,585	3,940	50.8	17,400	4,390	50.3	17,300	4,660	50.2	17,210	5,340	31.2	17,110	5,600	31.1	17,020	6,370	24.8	15,900	6,680	23.2	15,400	6,700	22.5					
	15	19,970	2,990	57.4	19,285	3,190	55.5	18,600	3,430	53.6	18,500	3,860	53.4	18,400	4,420	53.2	18,120	4,720	52.5	17,920	5,320	32.5	17,760	5,480	32.3	17,500	6,360	25.5	15,900	6,360	23.2	15,400	6,360	22.5					
	20	20,400	2,660	58.0	19,770	2,930	56.9	19,140	3,280	55.2	18,975	3,730	54.8	18,810	4,340	54.4	18,610	4,580	54.0	18,400	4,960	33.4	18,210	5,260	33.1	17,600	6,050	25.6	15,900	6,050	23.2	15,100	6,040	22.1					
	25	20,830	2,420	58.0	20,255	2,690	58.0	19,680	3,060	56.7	19,450	3,420	56.2	19,220	3,880	55.6	19,100	4,280	55.4	19,050	4,800	34.5	18,800	5,110	34.2	17,600	5,480	25.6	15,900	5,480	23.2	15,000	5,470	21.9					
	30	22,110	2,280	58.0	21,565	2,560	58.0	21,020	2,960	58.0	20,745	3,390	58.0	20,470	3,990	58.0	20,300	4,250	58.0	20,010	4,750	36.3	19,600	5,050	35.6	17,600	5,050	25.6	15,900	5,050	23.2	14,900	5,050	21.8					
	35	23,560	2,190	58.0	22,945	2,490	58.0	22,330	2,900	58.0	21,830	3,300	58.0	21,330	3,860	58.0	21,160	4,150	58.0	20,500	4,540	37.2	19,600	4,600	35.6	17,600	4,600	25.6	15,900	4,600	23.2	14,750	4,600	21.6					
	-25	9,800	4,830	28.2	10,650	5,630	30.7	11,500	6,570	33.2	11,050	6,680	31.9	10,600	6,790	30.7	10,370	6,950	30.1	9,800	6,950	17.8	9,390	6,950	17.1	8,800	6,720	12.8											
-20	13,300	6,240	38.3	13,135	6,570	37.8	12,970	6,940	37.4	12,500	7,030	36.1	12,400	7,460	35.9	12,300	7,730	35.7	12,100	7,900	21.9	11,700	8,540	21.3	11,500	8,850	16.7												
-15	14,980	6,350	43.1	14,370	6,620	41.4	13,760	6,950	39.7	13,450	7,000	38.8	13,100	7,020	37.9	12,850	7,130	37.3	12,560	7,550	22.8	12,260	8,100	22.3	11,860	8,140	17.3	10,800	7,990	15.8									
-10	15,000	5,880	43.1	14,380	6,030	41.4	13,750	6,190	39.6	13,400	6,490	38.7	13,050	6,830	37.8	12,650	6,840	36.7	12,200	6,850	22.1	11,820	7,250	21.5	11,720	7,560	17.1	11,000	7,490	16.1	10,500	7,760	15.4						
-7	14,800	5,150	42.6	14,400	5,360	41.5	14,000	5,600	40.4	13,960	6,080	40.3	13,910	6,640	40.2	13,800	6,830	40.0	12,820	6,850	23.2	12,030	7,120	21.9	11,800	7,420	17.2	11,030	7,500	16.1	10,340	7,600	15.1						
-2	14,500	4,460	41.7	14,630	4,740	42.1	14,760	5,050	42.6	14,690	5,730	42.4	14,610	6,610	42.3	14,300	6,590	41.5	13,400	6,450	24.3	12,650	6,800	23.0	12,060	6,850	17.6	11,330	6,950	16.5	10,500	7,050	15.4						
2	14,200	3,790	40.8	14,850	4,210	42.8	15,500	4,700	44.7	15,250	5,210	44.0	15,000	5,880	43.4	14,600	6,120	42.3	14,000	6,060	25.4	13,610	6,770	24.7	13,290	6,780	19.4	12,240	6,800	17.9	11,510	6,850	16.8						
7	17,500	3,110	50.3	16,750	3,310	48.2	16,000	3,550	46.2	16,000	4,000	46.2	16,000	4,570	46.3	16,000	4,940	46.4	16,000	5,520	29.0	16,000	5,930	29.1	16,000	6,540	23.3	16,000	7,550	23.4	16,000	8,510	23.4						
12	18,520	3,050	53.3	18,150	3,290	52.3	17,770	3,580	51.2	17,585	3,940	50.8	17,400	4,390	50.3	17,300	4,660	50.2	17,210	5,340	31.2	17,110	5,600	31.1	17,020	6,370	24.8	16,920	7,170	24.7	16,780	7,360	24.6						
15	19,970	2,990	57.4	19,285	3,190	55.5	18,600	3,430	53.6	18,500	3,860	53.4	18,400	4,420	53.2	18,120	4,720	52.5	17,920	5,320	32.5	17,760	5,480	32.3	17,600	6,420	25.6	17,400	7,020	25.4	17,000	7,110	24.9						
20	20,400	2,660	58.0	19,770	2,930	56.9	19,140	3,280	55.2	18,975	3,730	54.8	18,810	4,340	54.4	18,610	4,580	54.0	18,400	4,960	33.4	18,210	5,260	33.1	18,050	6,220	26.3	17,750	6,830	25.9	17,420	7,050	25.5						
25	20,830	2,420	58.0	20,255	2,690	58.0	19,680	3,060	56.7	19,450	3,420	56.2	19,220	3,880	55.6	19,100	4,280	55.4	19,050	4,800	34.5	18,800	5,110	34.2	18,600	5,810	27.1	18,300	6,350	26.7	17,900	6,680	26.2						
30	22,110	2,280	58.0	21,565	2,560	58.0	21,020	2,960	58.0	20,745	3,390	58.0	20,470	3,990	58.0	20,300	4,250	58.0	20,010	4,750	36.3	19,750	5,100	35.9	19,520	5,660	28.4	19,090	6,120	27.9	18,650	6,390	27.3						
35	23,560	2,190	58.0	22,945	2,490	58.0	22,330	2,900	58.0	21,830	3,300	58.0	21,330	3,860	58.0	21,160	4,150	58.0	20,750	4,620	37.6	20,430	4,840	37.1	20,260	5,350	29.5	19,960	5,870	29.1	19,590	6,220	28.7						

- Heating capacity
 - Capacity is according to EN14511.
 - Valid for heated water range ($\Delta T = \text{Leaving water temperature} - \text{Entering water temperature}$)
 - : If $LWT \leq 50^\circ C$, $\Delta T = 5^\circ C$ or $50^\circ C < LWT \leq 60^\circ C$, $\Delta T = 8^\circ C$ or $LWT > 60^\circ C$, $\Delta T = 10^\circ C$, within the minimum ~ maximum water flow rate.
- Cooling capacity
 - Capacity is according to EN14511
 - Valid for cooling water range ($\Delta T = \text{Entering water temperature} - \text{Leaving water temperature}$)
 - : $\Delta T = 5^\circ C$, within the minimum ~ maximum water flow rate.
- Power input : Power input is according to EN1451
- Peak capacity : Tested without defrost operation in accordance with EN14511.
 - ※ The real capacity would be changed according to the install environment.