



HYD 3K~6K-ES

3000/3600/4000/4600/5000/6000

Single-Phase Energy storage integrated inverter

- Outdoor IP65 design
- Compatible with on grid and off grid
- A variety of work modes are optional
- EPS function, switching time is less than 10ms
- Built-in zero export function
- Flexible configuration of lead acid or lithium battery
- Integrated fanless self-recognition heat dissipation design

Datasheet

	HYD 3000-ES	HYD 3600-ES	HYD 4000-ES	HYD * 4600-ES	HYD 5000-ES	HYD 6000-ES
--	-------------	-------------	-------------	---------------	-------------	-------------

	HYD 3000-ES	HYD 3600-ES	HYD 4000-ES	HYD * 4600-ES	HYD 5000-ES	HYD 6000-ES
Battery Parameters						
Battery Type	Lithium-ion, Lead-acid					
Nominal battery voltage	48V					
Battery voltage range	42-58V					
Battery Capacity	50-2000Ah					
Maximum Charging / Discharging Power	3000W					
Maximum Charging Current	65A (Programmable)					
Maximum Discharging Current	70A (Programmable)					
Charging curve(Lithium-ion)	BMS					
Charging curve(Lead-acid)	3-Stage adaptive with maintenance					
Depth of discharge	Lithium-ion: 0-90% DOD adjustable, Lead-acid: 0-50% DOD adjustable					
Input DC(PV side)						
Recommended Max. PV input power	3990Wp	4790Wp	5320Wp	6120Wp	6650Wp	7980Wp
Max DC power for single MPPT	2000W	2400W	2600W	2800W	3000W	3500W
Max. input voltage	600V					
Start-up voltage	120V					
Nominal DC Voltage	360V					
MPPT operating voltage range	90-580V					
Full power MPPT voltage range	160V-520V	180V-520V	200V-520V	230V-520V	250V-520V	300V-520V
MPPT number	2					
The max DC input current	12A/12A					
The max DC input short current	15A/15A					
Output AC(Grid side)						
Rated Power	3000W	3680W	4000W	4600W	5000W	6000W
Max. Output Power	3000VA	3680VA	4000VA	4600VA	5000VA	6000VA
Nominal Grid Voltage	L/N/PE, 220, 230, 240					
Operation phase	Single (L-N-PE)					
Max. Input / Output current	13.7A	16A	18.2A	21.0A	22.8A	27.3A
AC voltage Range	180V~276V (According to local standard)					
Grid Frequency range	44-55Hz/54-66Hz (According to local standard)					
THD	< 3%					
Power factor	1 default (+/-0.8 adjustable)					
Output AC(Emergency Power Supply)						
EPS rated power	3000VA					
Operation phase	Single (L-N-PE)					
EPS rated voltage, Frequency	230V, 50/60Hz					
EPS rated current	13.2A					
Peak Output Apparent Power	4000VA, 10s					
THD	< 3%					
Switch time	10ms default					
Efficiency						
MPPT efficiency	99.9%					
Max efficiency of solar Inverter	97.6%	97.6%	97.6%	97.8%	97.8%	98.0%
European efficiency of solar Inverter	97.2%	97.2%	97.2%	97.3%	97.3%	97.5%
Max. Charging efficiency of battery	94.6%					
Max. DisCharging efficiency of battery	94.6%					
Protection						
PV reverse polarity protection	Yes					
PV insulation detection	Yes					
Ground fault monitoring	Yes					
Over current protection	Yes					
Over voltage protection	Yes					
Battery soft start protection	Yes					
SPD protection	III					
General Data						
Ambient temperature range	-25 ~ +60 (Above 45°C Derating)					
Standby Losses	< 10W					
Topology	High frequency insulation (for bat)					
DC-Switch	Yes					
Degree Of Protection	IP65					
Allowable Relative Humidity Range	0~100%					
Communication	RS485, Wifi/Ethernet/GPRS, SD, CAN2.0					
Protective class	Class I					
Max. Operating Altitude	2000m					
Current Sensor Connection	External					
Noise	< 25dB					
Weight	20.5kg					
Cooling	Natural					
Dimension (W*H*D)	566*394*173 mm					
Display	LCD display					
Warranty	5 Years or more					
Standard						
EMC	EN 61000-6-2, EN 61000-6-3, EN 61000-3-2, EN 61000-3-3, EN 61000-3-11, EN 61000-3-12					
Safety standards	IEC62109-1/2, IEC62040-1, IEC62116, IEC61727, IEC-61683, IEC60068(1,2,14,30)					
Grid standards	AS/NZS 4777, VDE V 0124-100, V 0126-1-1, VDE-AR-N 4105, CEI 0-21, EN50549, GB3/G59/G98/G99, UTE C15-712-1, UNE 206 007-1					

The models marked with "*" should be available only for some designated countries.