

ATTESTATION OF CONFORMITY

Issued to: Ginlong Technologies Co., Ltd.
No. 57 Jintong Road, Binhai Industrial Park, Xiangshan, Ningbo, Zhejiang, 315712,
P.R. China.

For the product: Grid-connected PV inverter



Trade name:

Type/Model: Solis-mini-700-4G, Solis-mini-1000-4G, Solis-mini-1500-4G, Solis-mini-2000-4G,
Solis-mini-2500-4G, Solis-mini-3000-4G, Solis-mini-3600-4G
S5-GR1P0.7K-M, S5-GR1P1K-M, S5-GR1P1.5K-M, S5-GR1P2K-M,
S5-GR1P2.5K-M, S5-GR1P3K-M, S5-GR1P3.6K-M

Ratings: See Annex

Manufactured by: Ginlong Technologies Co., Ltd.
No. 57 Jintong Road, Binhai Industrial Park, Xiangshan, Ningbo, Zhejiang, 315712,
P.R. China.

Requirements: NRS 097-2-1:2017 (Edition 2.1 July 2020)

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 6092293.51

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

Arnhem, 8 January 2021

Number: 6092293.02AOC

DEKRA Testing and Certification (Shanghai) Ltd.

Kreny Lin
Certification Manager

A handwritten signature in black ink, appearing to read "Kreny Lin".

© Integral publication of this attestation and adjoining reports is allowed

Page 1 of 2

DEKRA Testing and Certification (Shanghai) Ltd.
3F #250 Jiangchangsan Road Shibe Hi-Tech Park, 200436 Jing'an District, Shanghai, China
T +86 21 6056 7666 F +86 21 6056 7555 www.dekra-product-safety.com

Ratings of the test product:

Operating temperature range: - 25°C to + 60°C

Protective class: I

Ingress protection rating: IP65

Power factor range (adjustable): 0.8 leading...0.8 lagging

Solis-mini-700-4G:

PV input: max 600Vdc, MPP voltage range: 50–500Vdc, max 11A, I_{sc} PV: 17,2A

AC output: 230V, 50Hz, max 4,4A, 800W

Solis-mini-1000-4G:

PV input: max 600Vdc, MPP voltage range: 50–500Vdc, max 11A, I_{sc} PV: 17,2A

AC output: 230V, 50Hz, max 5,2A, 1100W

Solis-mini-1500-4G:

PV input: max 600Vdc, MPP voltage range: 50–500Vdc, max 11A, I_{sc} PV: 17,2A

AC output: 230V, 50Hz, max 8,1A, 1700W

Solis-mini-2000-4G:

PV input: max 600Vdc, MPP voltage range: 80–500Vdc, max 11A, I_{sc} PV: 17,2A

AC output: 230V, 50Hz, max 10,5A, 2200W

Solis-mini-2500-4G:

PV input: max 600Vdc, MPP voltage range: 80–500Vdc, max 11A, I_{sc} PV: 17,2A

AC output: 230V, 50Hz, max 13,3A, 2800W

Solis-mini-3000-4G:

PV input: max 600Vdc, MPP voltage range: 80–500Vdc, max 11A, I_{sc} PV: 17,2A

AC output: 230V, 50Hz, max 15,7A, 3300W

Solis-mini-3600-4G:

PV input: max 600Vdc, MPP voltage range: 80–500Vdc, max 19A, I_{sc} PV: 30A

AC output: 230V, 50Hz, max 16A, 3600W

S5-GR1P0.7K-M:

PV input: max 600Vdc, MPP voltage range: 50–500Vdc, max 12.5A, I_{sc} PV: 17.2A

AC output: 230V, 50Hz, max 4,4A, 800W

S5-GR1P1K-M:

PV input: max 600Vdc, MPP voltage range: 50–500Vdc, max 12.5A, I_{sc} PV: 17,2A

AC output: 230V, 50Hz, max 5,2A, 1100W

S5-GR1P1.5K-M:

PV input: max 600Vdc, MPP voltage range: 50–500Vdc, max 12.5A, I_{sc} PV: 17,2A

AC output: 230V, 50Hz, max 8,1A, 1700W

S5-GR1P2K-M:

PV input: max 600Vdc, MPP voltage range: 80–500Vdc, max 12.5A, I_{sc} PV: 17,2A

AC output: 230V, 50Hz, max 10,5A, 2200W

S5-GR1P2.5K-M:

PV input: max 600Vdc, MPP voltage range: 80–500Vdc, max 12.5A, I_{sc} PV: 17,2A

AC output: 230V, 50Hz, max 13,3A, 2800W

S5-GR1P3K-M:

PV input: max 600Vdc, MPP voltage range: 80–500Vdc, max 12.5A, I_{sc} PV: 17,2A

AC output: 230V, 50Hz, max 15,7A, 3300W

S5-GR1P3.6K-M:

PV input: max 600Vdc, MPP voltage range: 80–500Vdc, max 19A, I_{sc} PV: 30A

AC output: 230V, 50Hz, max 16A, 3600W