

Support brackets for outdoor installation

Support bracket

WK 1



Corrosion-protected wall mounting support made from zinc-plated steel for on-site installation. Height adjustments can be made on the wall rail, while the appliance rail provides the possibility to align the appliance. Standard delivery includes: 2 pce, incl. anti-vibration mounts and 2 m ribbon heater.

		WK 1
		232963
Support length	mm	740
Weight	kg	10
Weight	kg	120
Suitable for		10 AC(S), 15/25 I(S)-2, 15/25 IK(S)-2, classic

WK 2



Corrosion-protected wall mounting support made from zinc-plated steel for on-site installation. Height adjustments can be made on the wall rail, while the appliance rail provides the possibility to align the appliance. Standard delivery includes: 2 pce, incl. anti-vibration mounts.

		WK 2
		234722
Support length	mm	950
Weight	kg	175
Suitable for		15/20/25 AC(S)

SK 1



SK 1: Stainless steel, T-shaped support for floorstanding, concrete-embedded installation. Standard delivery includes: 2 pce incl. installation aid for a defined clearance dimension, anti-vibration mounts, plus 1 m ribbon heater. SK 2: White powder-coated bracket for installation on a strip foundation. Standard delivery includes: 2 pce incl. screws for securing the heat pump to the bracket.

		SK 1
		232964
Height	mm	950
Depth	mm	570
Weight	kg	175
Suitable for		10 AC(S), 15/25 I(S)-2, 15/25 IK(S)-2 and 15/20/25 AC(S)

MK 1



Corrosion-protected support for floor mounting in matching design, including anti-vibration mounts. For weather-proof connection of the heat pump.

		MK 1
		233047
Height	mm	254
Width	mm	1260
Depth	mm	575
Suitable for		10 AC(S), 15 AC(S)